Specification Sheet

SOLYX UltraCool®

UltraCool-S6060 60% VLT Silver Window Film



Product Details

UltraCool-S6060 NOMINAL HEAT REJECTION Film. UltraCool-S6060 60% VLT Light Silver window film maintains high light transmission while rejection 43% Solar heat This film also blocks out 99% of the UV rays! Not very noticeable on windows!

Flammability Rating

This product meets **Class B, s1, d0,** as specified in **BS EN 13501-1:2018.**

This product meets ASTM E84 and is classified as Class A as defined in NFPA 101, Life Safety Code®.

Specification

Product Code	UltraCool-S6060
Film Type	Polyester
Adhesive Type	Acrylic, Pressure-Sensitive
Usage	Interior
Available Roll Width(s)	60”
Thickness	51 micron
Shading Coefficient	.66
Visible Light Reflectance	13.6%
Visible Light Transmission	68%
UV Transmission	<1%
Total Solar Energy Absorbed	28%
Total Solar Energy Rejected	43%

Installation & Warranty

Installation

Installation should be in accordance with the manufacturer’s installation instructions. This film is applied using the same methods used for installing window films.

Warranty

This product will be free from defects in material and manufacture for a period of five (5) years from the date of installation. See warranty information for specific details.

To ensure that **Genuine Solyx®** products have been installed, proof of a valid invoice number is required to validate your warranty. Scan the QR code below or visit www.glassfilms.eu/validate to validate.

Product Construction

Face Film

51 micron Metalized Polyester

Adhesive

Solvent Acrylic, Pressure Sensitive

Release Liner

Transparent Synthetic

Distribution & Contact Information

Solyx® Decorative Films are available through authorised window film installers and signage companies, or directly from Glass Films.

Contact Information

Glass Films

Tel: +44 (0) 800 970 6366
Email: sales@glassfilms.eu
Web: www.glassfilms.eu

Solyx® & Simglas® are trademarks of Decorative Films LLC. © Glass Films 2022, All Rights Reserved.