Specification Sheet

SOLYX UltraGlare®

UltraGlare-G006 Dark Shade



Product Details

UltraGlare-G006 Dark Shade. Transparent, optically clear, UV stabilized, coloured, glare control polyester film with scratch resistant protective coating. Suitable for glare reduction.

Flammability Rating

This product meets **Class B, s1, d0,** as specified in **BS EN 13501-1:2018.**

This product meets ASTM E84 and is classified as Class A as defined in NFPA 101, Life Safety Code®.

Specification

Product Code	UltraGlare-G006
Film Type	Polyester
Adhesive Type	Acrylic Pressure Sensitive
Usage	Interior
Available Roll Width(s)	60”
Thickness	51 micron
Shading Coefficient	.66
Visible Light Reflectance	4%
Visible Light Transmission	7%
UV Transmission	0%
Glare Reduction	93%
Total Solar Energy Absorbed	48%
Total Solar Energy rejected	47%

Installation & Warranty

Installation

Installation should be in accordance with the manufacturer’s installation instructions. This film is applied using the same methods used for installing window films.

Warranty

This product will be free from defects in material and manufacture for a period of five (5) years from the date of installation. See warranty information for specific details.

To ensure that **Genuine Solyx®** products have been installed, proof of a valid invoice number is required to validate your warranty. Scan the QR code below or visit www.glassfilms.eu/validate to validate.

Product Construction

Face Film

51 micron Non-Reflective Polyester

Adhesive

Solvent Acrylic Pressure Sensitive

Release Liner

Transparent Synthetic

Distribution & Contact Information

Solyx® Decorative Films are available through authorised window film installers and signage companies, or directly from Glass Films.

Contact Information

Glass Films

Tel: +44 (0) 800 970 6366

Email: sales@glassfilms.eu

Web: www.glassfilms.eu

Solyx® & Simglas® are trademarks of Decorative Films LLC. © Glass Films 2022, All Rights Reserved.